



# Acoustic Network™ Manager ANM2005

A PC equipped with LogiSon™ Acoustic Network™ Manager Software can be used to communicate with the Network when linked to the Control Panel by Ethernet. The user has the ability to control up to 99 Network Control Panels from one location. The PC's large screen allows more information to be displayed simultaneously, permitting a greater range of adjustment than is directly available through the Control Panel. The user-friendly Software can be used to perform Network configuration and to establish the masking, paging/music, timer and keypad settings. These settings can be saved or printed for diagnostic or record-keeping purposes.



## Control Performance

Functions Communication setup, Network setup, masking, paging, timer, keypad settings, file management, diagnostics and reporting.

## Masking Performance

Volume 35 to 85 dBA, 0.5 dBA steps, mute  
Equalization 1/3-octave, 23 bands  
Preset Contours 50 options

## Paging Performance

Zone Configuration Zone 1, 2, 3 or mute (per Primary Hub)  
Volume 35 to 85 dBA, 0.5 dBA steps, mute  
Equalization 1/1-octave, 8 bands  
Preset Contours 50 options

## Timer Performance

Number of Zones 1 to 9  
Size of Zones Unrestricted  
Timer Schedules Unique schedules for each weekday  
Volume Changes Per Day 9  
Rate of Change 0 to 9 minutes per increment  
Volume Increments 0.5 dBA steps  
Introductory Ramp Up 1 to 15 day user-defined schedule; option of 0.5 or 1 dBA steps  
Exception Schedules 3 user-defined schedules; up to 30 exception dates  
Delayed-On Feature Yes  
Daylight Savings Adjustment Automatic; option of preset international or user-defined schedule